

# HMX 8

MARINE COAX

200 W




## TECHNICAL SPECIFICATIONS

<b>Component</b>	Two way coaxial	
<b>Size</b>		
Woofers	mm (in.)	200 (8)
Tweeter diaphragm	mm (in.)	36 (1.4)
<b>Voice Coil Ø</b>		
Woofers	mm (in.)	32 (1.26)
Tweeter	mm (in.)	20 (0.8)
<b>Power Handling</b>	W peak	200
	W continuous	100
<b>Impedance</b>	Ω	4
<b>Frequency Response</b>	Hz	45 ÷ 25k
<b>Woofers Magnet size D x d x h</b>	mm (in.)	90 x 40 x 20 (3.54 x 1.57 x 0.79)
<b>Tweeter Magnet size D x h</b>	mm (in.)	19,7 x 3 (0.78 x 0.12)
<b>Weight of one speaker</b>	kg (lb.)	-
<b>Woofers Magnet</b>	High density flux ferrite	
<b>Tweeter Magnet</b>	Neodymium	
<b>Cone</b>	Polypropylene with UV inhibitors	
<b>Dome</b>	PEI	
<b>Xmech</b>	mm (in.)	±8,5 (0.33)

## ELECTRO-ACOUSTIC PARAMETERS

<b>D</b>	mm	200
<b>Xmax</b>	mm	4.5
<b>Re</b>	Ω	3.5
<b>Fs</b>	Hz	55
<b>Le</b>	mH	0.4
<b>Vas</b>	l	17
<b>Mms</b>	g	25
<b>Cms</b>	mm/N	0.34
<b>BL</b>	T·m	6,2
<b>Qts</b>		0.67
<b>Qes</b>		0.72
<b>Qms</b>		9.5
<b>Spl</b>	dB	91

1. Engineered and tested for the real environment of application (UV, salt-fog, vibrations, water spray, thermal shock, dust).
2. 1.4" Neodymium magnet tweeter featuring a PEI material dome combined with faceplate and acoustic lens optimized for best off-axis dispersion and highest SPL.
3. Sound-transparent stainless steel tweeter mesh grille providing efficient high-frequency transfer, attractive look and a rock-solid protection.
4. Long-throw 32 mm (1.26") voice coil woofer fine-tuned for infinite baffle application featuring polypropylene cone injected with UV inhibitors and co-molded Santoprene surround.
5. Aramid fiber spider with silicone-insulated lead wires ensuring durability and constant performance over time.
6. FEM optimized high-excursion mobile equipment driven by a massive magnetic group encapsulated into a marine-grade polymer injected basket.
7. Sealed built-in crossover with resettable solid-state tweeter protection circuit.
8. Gold-plated corrosion resistant terminals.



<b>A</b>	255 mm	8.86 in.
<b>B</b>	180 mm	7.09 in.
<b>C</b>	123 mm	4.84 in.
<b>D</b>	91 mm	3.58 in.
<b>F</b>	30,3 mm	1.19 in.

